


Pushbutton Units and Indicator Lights




30 mm Heavy Duty, Watertight/Oiltight, Class 52

Accessories and spare parts

Selection and ordering data

Version	Suitable for	Lamp voltage	Color	Order no.	List Price
					\$
Lamps with screw connection, miniature bayonet (BA 9s style)					
Incandescent lamps,					
	Flashing, type 267 lamp (replaces 755 lamp)	51, 52	6 V	52AABNF	11.60
	6V type 755 lamp	51, 52	6 V	52AABN	7.70
	12V type 756	51, 52	12 V	52AACN	7.70
	24V type 757	51, 52	24 V	52AADN	7.00
	120V, 2.5W, type #120MB	52	120 V	52AAENC1	7.70
	Neon (uses resistors) type B2A (NE-51H)	52	120 V	52AAPN	15.90
Candelabra, 120 V, Full voltage type 3S6/5 ¹⁾	52 older revision styles	120 V		52AAENC	7.70
LED's BA9s Style	52	6 V	red	52AEB2	21.00
	52	6 V	green	52AEB3	21.00
	52	6 V	yellow	52AEB4	21.00
	52	6 V	white	52AEBB	21.00
	52	6 V	blue	52AEB5	21.00
	52	24 V	red	52AED2	21.00
	52	24 V	green	52AED3	21.00
	52	24 V	yellow	52AED4	21.00
	52	24 V	white	52AEDB	21.00
	52	24 V	blue	52AED5	21.00
	52	120 V	red	52AEE2	21.00
	52	120 V	green	52AEE3	21.00
	52	120 V	yellow	52AEE4	21.00
	52	120 V	white	52AEEB	21.00
	52	120 V	blue	52AEE5	21.00
LED's, cluster type For use with Class 52 pilot lights only	52	6 V	red	52AEB27	26.50
	52	6 V	green	52AEB37	26.50
	52	6 V	yellow	52AEB47	26.50
	52	24 V	red	52AED27	26.50
	52	24 V	green	52AED37	26.50
	52	24 V	yellow	52AED47	26.50
	52	120 V	red	52AEE27	26.50
	52	120 V	green	52AEE37	26.50
	52	120 V	yellow	52AEE47	26.50

Touchsafe contact blocks with gold flashing

	52 BAJ	1 NO 1 NC		52BAK	11.60	
		52 BAK	1 NO - 1 NC 1 NO early make 1 NC late break	closes before 52BAK opens after 52 BAJ	52BAJ	11.60
		52 BAK	1 NO - 1 NC	Reed switch	52BJK	23.20
	52 BAR	1 NC extra late break	UL listed for class 1 division 2 .25A Max, 150V AC, 10 Watt max .5A Max, 150V DC, 10 Watt max	52BAH	11.60	
			52BAE	11.60		
				52BAR²⁾	46.40	
				52BAU	11.60	

1) Design change made in 2003 from candelabra to BA 9s type bulbs. Contact technical support for further information.

2) Hermetically sealed.